



INSTRUCTIONS FOR:

BENCH MOUNTED SHEET METAL BENDER MODEL No: DF760.V2

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE.

Bench mounted sheet metal folder, fitted with mounted plates. Capable of bending up to 17 gauge steel sheet. Ideal for the small garage or restoration operation.

Maximum sheet size: 760mm Maximum sheet thickness: 17gauge Maximum bending angle: 90 degrees Length of unit: 800mm Width of unit: 150mm Height of unit: 73mm

SAFETY INSTRUCTIONS

- Wear approved safety goggles when operating the sheet metal bender. Your local Sealey dealer offers a complete range of safety equipment.
- Use the tool only for its intended purpose.
- Check all items of the sheet metal bender regularly for damaged parts. DO NOT use if any of its components are broken, worn or damaged.
- Use original Sealey spare parts and accessories. Use of non-recommended spare parts may be dangerous and will invalidate warranty.
- DO NOT operate this tool while tired, under the influence of drugs, alcohol or other impairing medication.
- X DO NOT allow unqualified persons to operate the metal folder. Keep children away from the tool.

2. ASSEMBLY

Unpack the unit and check that all parts are included and not damaged. Should you experience a problem contact your supplier immediately. Note: Numbers in brackets refer to item numbers on the parts diagram.

- The stand (1) should be secured to a work bench using the mounting holes and 4 bolts (3/8" diameter).
- 2.2 Each handle ball (7) should be attached to the handle lever (6) and the handle levers should be placed into the pins (5).

OPERATION 3.


- To use the bender, lower the handle lever until the moving plate is parallel to the work bench. Position the material to be bent on the supporting plate (2) and the moving plate (4) and properly align with the edge to be bent up against the back edge of the supporting plate.
- 3.2 Place and secure the pressing plate (3) on top of the supporting plate with the back edge of pressing plate aligned with back edge of supporting plate. Suitable clamps (not included) are required to secure the pressing plate. For a full range of clamps see your authorised Sealey dealer.
- 3.3 Raise the two handle levers to bend the material to the desired angle.
- When the folder is not in use, it should be covered and stored in a dry location.

Item	Part No.	Description

PARTS

DF760.V2-01 Stand Complete (includes items 1, 2, 4 & 5)

3 DF760 V2-03 Pressing plate 6 DF760.V2-06 Handle lever 7 DF760 V2-07 Handle knob



NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. IMPORTANT: No responsibility is accepted for incorrect use of this product.

WARRANTY: Guarantee is 12 months from purchase date. Proof of purchase will be required for any claim.

INFORMATION: Please call us for a copy of our latest catalogue.





Sole U.K. Distributor **Sealey Group** Bury St. Edmunds Suffolk.



01284 757500 01284 703534



www.sealey.co.uk



sales@sealey.co.uk